



## 1. Identification of the material and supplier

<b>Product name</b>	<b>Marine Naval Fuel F76</b>
<b>SDS no.</b>	0000003656
<b>Historic SDS no.</b>	YSTMO
<b>Product use</b>	Diesel fuel for marine applications, conforming to DEF (AUST) 5213A.
<b>Supplier</b>	BP Australia Pty Ltd (ABN 53 004 085 616) 717 Bourke Street Docklands VIC 3008 Australia Tel: +61 (03) 9268 4111 Fax: +61 (03) 9268 3321
<b>EMERGENCY TELEPHONE NUMBER</b>	1800 638 556
<b>Product code</b>	0000003656

## 2. Hazards identification

<b>Statement of hazardous/dangerous nature</b>	HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS.
<b>Risk phrases</b>	R40- Limited evidence of a carcinogenic effect. R65- Harmful: may cause lung damage if swallowed.
<b>Safety phrases</b>	S2- Keep out of the reach of children. S24- Avoid contact with skin. S29- Do not empty into drains. S36/37- Wear suitable protective clothing and gloves. S43- In case of fire, use water, dry chemical powder or carbon dioxide. Do not use water jet. S61- Avoid release to the environment. Refer to special instructions/safety data sheet. S62- If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

## 3. Composition/information on ingredients

May also contain small quantities of proprietary performance additives. Contains small amounts of diethyleneglycol monomethyl ether (DEGME, 2-(2-methoxyethoxy)ethanol ) as a fuel icing inhibitor.

<b>Ingredient name</b>	<b>CAS no.</b>	<b>%</b>
Fuels, diesel	68334-30-5	100
Contains small quantities of polycyclic aromatic hydrocarbons (PAHs).		
Other ingredients, determined not to be hazardous according to Safe Work Australia criteria, and not dangerous according to the ADG Code, make up the product concentration to 100%.		

## 4. First-aid measures

<b>Eye contact</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention if irritation occurs.
<b>Skin contact</b>	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
<b>Inhalation</b>	If inhaled, remove to fresh air. Get medical attention.
<b>Ingestion</b>	Do not induce vomiting. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Aspiration hazard if swallowed. Can enter lungs and cause damage. Get medical attention.
<b>Advice to doctor</b>	Treatment should in general be symptomatic and directed to relieving any effects. Product can be aspirated on swallowing or following regurgitation of stomach contents, and can cause severe and potentially fatal chemical pneumonitis, which will require urgent treatment. Because of the risk of aspiration, induction of vomiting and gastric lavage should be avoided. Gastric lavage should be undertaken only after endotracheal intubation. Monitor for cardiac dysrhythmias.

Note: High Pressure Applications  
Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent

## 5. Fire-fighting measures

### Extinguishing media

**Suitable** In case of fire, use water fog, foam, dry chemical or carbon dioxide extinguisher or spray.

**Not suitable** Do not use water jet.

**Hazardous decomposition products** Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
other hazardous substances.

**Unusual fire/explosion hazards** Combustible liquid and vapour. Vapour may cause flash fire. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

**Special fire-fighting procedures** Do not fight fire when it reaches the material. Withdraw from fire and let it burn. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. First move people out of line-of-sight of the scene and away from windows.

**Protection of fire-fighters** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. Accidental release measures

**Personal precautions** No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

**Environmental precautions** Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

**Large spill** Stop leak if without risk. Eliminate all ignition sources. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

**Small spill** Stop leak if without risk. Eliminate all ignition sources. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

## 7. Handling and storage

**Handling** Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not ingest. If ingested, do not induce vomiting. Never siphon by mouth. Avoid breathing vapours, spray or mists. Use only with adequate ventilation. Keep away from heat, sparks and flame. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Avoid contact of spilt material and runoff with soil and surface waterways. Wash thoroughly after handling. When using do not eat, drink or smoke.

**Storage** Keep container tightly closed. Keep container in a cool, well-ventilated area. Store and use only in equipment/containers designed for use with this product. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packaging and should not be removed. Do not enter storage tanks without breathing apparatus unless the tank has been well ventilated and the tank atmosphere has been shown to contain hydrocarbon vapour concentrations of less than 1% of the lower flammability limit and an oxygen concentration of at least 20% volume. Always have sufficient people standing by outside the tank with appropriate breathing apparatus and equipment to effect a quick rescue.

**Combustibility Classification** Combustible liquid Class C1 (AS 1940).

**Additional information- Storage** This product must be handled in compliance with Australian Standard: The storage and handling of flammable and combustible liquids [Standard 1940-2004 as amended and adapted].

Light hydrocarbon vapours can build up in the headspace of tanks. These can cause flammability/explosion hazards even at temperatures below the normal flash point (note: flash point must not be regarded as a reliable indicator of the potential flammability of vapour in tank headspaces). Tank headspaces should always be regarded as potentially flammable and care should be taken to avoid static electrical discharge and all ignition sources during filling, ullaging and sampling from storage tanks.

Will present a flammability hazard if heated above flash point but bulk liquids at normal storage temperatures will present virtually no fire hazard. If fuel contacts hot surfaces, or leaks from high pressure fuel pipes, the vapour and/or mists generated will create a flammability or explosion hazard. Product contaminated rags, paper or material used to absorb spillages, represent a fire hazard, and should not be allowed to accumulate. Dispose of safely immediately after use.

Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Never weld, solder or braze empty containers.

## 8 . Exposure controls/personal protection

<b>Ingredient name</b>	<b>Occupational exposure limits</b>
Fuels, diesel	<b>ACGIH TLV (United States). Absorbed through skin.</b> TWA: 100 mg/m <sup>3</sup> , (measured as total hydrocarbons) 8 hour(s). Issued/Revised: 1/2007 Form: Total hydrocarbons

For information and guidance, the ACGIH values are included. For further information on these please consult your supplier.

<b>Biological Limit Values</b>	No biological limit allocated.
<b>Exposure controls</b>	
<b>Occupational exposure controls</b>	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable.
<b>Hygiene measures</b>	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.
<b>Personal protective equipment</b>	
<b>Respiratory protection</b>	Use only with adequate ventilation. Avoid breathing of vapours, mists or spray. Select and use respirators in accordance with AS/NZS 1715/1716. When mists or vapours exceed the exposure standards then the use of the following is recommended: Approved respirator with organic vapour and dust/mist filters. Filter capacity and respirator type depends on exposure level.
<b>Skin and body</b>	Avoid contact with skin and clothing. Wear clothing and footwear that cannot be penetrated by chemicals or oil.
<b>Hand protection</b>	Wear protective gloves if prolonged or repeated contact is likely. Recommended: Nitrile gloves.  The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.
<b>Eye protection</b>	Chemical splash goggles.

## 9 . Physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Colour</b>	Clear, Bright
<b>Odour</b>	Mild
<b>Flash point</b>	>61.5 °C (Closed cup) Pensky-Martens.
<b>Auto-ignition temperature</b>	240°C (464°F)
<b>Explosive properties</b>	Combustible liquid and vapour. Vapour may cause flash fire. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
<b>Explosion limits</b>	Lower: 0.7% Upper: 5%
<b>Vapour pressure</b>	<0.1 kPa (<0.75 mm Hg) at 20°C
<b>Vapour density</b>	Not available.
<b>Viscosity</b>	Kinematic: <7 mm <sup>2</sup> /s (<7 cSt) at 40°C
<b>pH</b>	Not available.
<b>Boiling point / range</b>	180 to 360°C (356 to 680°F)
<b>Melting point / range</b>	Not available.
<b>Relative density/Specific gravity</b>	0.84
<b>Density</b>	810 to 850 kg/m <sup>3</sup> (0.81 to 0.85 g/cm <sup>3</sup> ) at 15°C
<b>Solubility</b>	Insoluble

## 10 . Stability and reactivity

<b>Stability</b>	The product is stable.
<b>Conditions to avoid</b>	Avoid all possible sources of ignition (spark or flame). Avoid excessive heat.
<b>Incompatibility with various substances/Hazardous Reactions</b>	Reactive or incompatible with the following materials: oxidising materials.
<b>Hazardous decomposition products</b>	Decomposition products may include the following materials: carbon dioxide carbon monoxide other hazardous substances.

## 11 . Toxicological information

### Effects and symptoms

<b>Eyes</b>	Vapour, mist or fume may cause eye irritation. Exposure to vapour, mist or fume may cause stinging, redness and watering of the eyes.
<b>Skin</b>	Causes skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
<b>Inhalation</b>	Harmful if inhaled. May cause irritation of respiratory tract, coughing, shortness of breath.
<b>Ingestion</b>	Aspiration of this product into the lungs may cause chemical pneumonia and can be fatal. Aspiration into the lungs can occur while vomiting after ingestion of this product. Do not siphon by mouth. Irritating to mouth, throat and stomach.

### Chronic toxicity

<b>Carcinogenic effects</b>	POSSIBLE CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER, BASED ON ANIMAL DATA. -- Carcinogenic Category 3 Risk of cancer depends on duration and level of exposure.
<b>Mutagenic effects</b>	No known significant effects or critical hazards.
<b>Other information</b>	May cause damage to organs through prolonged or repeated exposure. Vapour, mists or fumes may contain polycyclic aromatic hydrocarbons some of which are known to produce skin cancer.  Diesel exhaust particulates have been classified by the National Toxicological Program (NTP) to be a reasonably anticipated human carcinogen. Exposure should be minimized to reduce potential risk.

## 12 . Ecological information





<b>Ecotoxicity</b>	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<b>Biodegradability</b>	
<b>Persistence/degradability</b>	This product is inherently biodegradable.
<b>Mobility</b>	Spillages may penetrate the soil causing ground water contamination. This material may accumulate in sediments.
<b>Bioaccumulative potential</b>	This product is not expected to bioaccumulate through food chains in the environment.
<b>Other ecological information</b>	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

## 13 . Disposal considerations

<b>Disposal considerations / Waste information</b>	The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
<b>Special Precautions for Landfill or Incineration</b>	Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packaging and should not be removed.

## 14 . Transport information

### International transport regulations

Regulatory information	UN number	Proper shipping name	Class	PG*	Label	Additional information
<b>ADG Classification</b>	Not regulated.	-	-	-	-----	<b>Remarks</b> Combustible liquid Class C1 (AS 1940).
<b>IMDG Classification</b>	UN 1202	DIESEL FUEL. Marine pollutant (Fuels, diesel)	3	III	 	<b>Emergency schedules (EmS)</b> F-E, S-E
<b>IATA/ICAO Classification</b>	UN 1202	DIESEL FUEL	3	III	 	-

PG\* : Packing group

Regulatory information	UN number	Proper shipping name	Class	PG*	Label	Additional information
------------------------	-----------	----------------------	-------	-----	-------	------------------------

**Special precautions for user** No known special precautions required. See Section: "Handling and storage" for additional information.

## 15 . Regulatory information

### Standard for the Uniform Scheduling of Medicines and Poisons

Not scheduled

Consumer products - This product is exempt per Appendix A of the SUSMP.  
 Industrial Products - Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with NOSHC National Code of Practice for labelling of workplace substances.

### Control of Scheduled Carcinogenic Substances

#### Ingredient name

#### Schedule

No Listed Substance

#### Other regulations

<b>REACH Status</b>	For the REACH status of this product please consult your company contact, as identified in Section 1.
<b>United States inventory (TSCA 8b)</b>	All components are listed or exempted.
<b>Australia inventory (AICS)</b>	All components are listed or exempted.
<b>Canada inventory</b>	All components are listed or exempted.
<b>China inventory (IECSC)</b>	All components are listed or exempted.
<b>Japan inventory (ENCS)</b>	All components are listed or exempted.
<b>Korea inventory (KECI)</b>	All components are listed or exempted.
<b>Philippines inventory (PICCS)</b>	All components are listed or exempted.

## 16 . Other information

### Key to abbreviations

AMP = Acceptable Maximum Peak  
 ACGIH = American Conference of Governmental Industrial Hygienists, an agency that promulgates exposure standards.  
 ADG = Australian Code for the Transport of Dangerous Goods by Road and Rail  
 ADG Code = Australian Code for the Transport of Dangerous Goods by Road and Rail  
 CAS Number = Chemical Abstracts Service Registry Number  
 HAZCHEM Code = Emergency action code of numbers and letters which gives information to emergency services. Its use is required by the ADG Code for Dangerous Goods in bulk.  
 ICAO = International Civil Aviation Organization.  
 IATA = International Air Transport Association, the organization promulgating rules governing shipment of goods by air.  
 IMDG = International Maritime Organization Rules, rules governing shipment of goods by water.  
 IP 346 = A chemical screening assay for dermal toxicity. The European Commission has recommended that Method IP 346 be used as the basis for labelling certain lubricant oil base stocks for carcinogenicity. The EU Commission has stipulated that the classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346. (See Note L, European Commission Directive 67/548/EEC as amended and adapted.) DMSO is a solvent.  
 NOHSC = National Occupational Health & Safety Commission, Australia  
 TWA = Time weighted average  
 STEL = Short term exposure limit  
 UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.

### History

<b>Date of issue</b>	27/10/2011.
<b>Date of previous issue</b>	10/03/2011.
<b>Prepared by</b>	Product Stewardship

### Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

<b>Product name</b> Marine Naval Fuel F76	<b>Product code</b> 0000003656	Page: 5/5
<b>Version 2</b>	<b>Date of issue</b> 27 October 2011	<b>Format</b> Australia (Australia)
		<b>Language</b> ENGLISH (ENGLISH)