

SAFETY DATA SHEET**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Product name	Residual Marine Fuel (RMA, RMB, RMD, RME, RMF & RMG)
Other means of identification	RMA 10, RMA 10LS, RMA 30, RMA 30LS RMB 30, RMB 30LS RMD 80, RMD 80LS RME 180, RME 180LS RMF 180, RMF 180LS RMG 180, RMG 180LS
SDS no.	SMI2112
Product type	Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	Fuel for industrial, marine and commercial boilers and furnaces; fuel for low and medium speed diesel engines. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
-------------------------------------	---

1.3 Details of the supplier of the safety data sheet

Supplier	BP Global Investments Salalah & Co LLC PO Box 2309 Postal Code 211 Salalah Sultanate of Oman
E-mail address	MSDSadvice@bp.com

1.4 Emergency telephone number

EMERGENCY TELEPHONE NUMBER	+968 23219350 (24 hours)
-----------------------------------	--------------------------

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Product definition	Mixture
<u>Classification according to Directive 1999/45/EC [DPD]</u>	

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification	Carc. Cat. 2; R45 Repr. Cat. 3; R63 Xn; R20, R48/21 Xi; R38 N; R50/53
-----------------------	---

Human health hazards	May cause cancer. Possible risk of harm to the unborn child. Also harmful by inhalation. Also harmful: danger of serious damage to health by prolonged exposure in contact with skin. Irritating to skin.
-----------------------------	--

Environmental hazards	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
------------------------------	--

See Section 16 for the full text of the R phrases or H statements declared above.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements**Hazard symbol or symbols**

Product name Residual Marine Fuel (RMA, RMB, RMD, RME, RMF & RMG)

Product code SMI2112

Page: 1/13

Version 1.02 **Date of issue** 6 August 2013

Format Rest of World
(Rest of World)

Language ENGLISH

SECTION 2: Hazards identification

Indication of danger

Dangerous for the environment

Risk phrases

R45- May cause cancer.
 R63- Possible risk of harm to the unborn child.
 R20- Also harmful by inhalation.
 R48/21- Also harmful: danger of serious damage to health by prolonged exposure in contact with skin.
 R38- Irritating to skin.
 R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases

S53- Avoid exposure - obtain special instructions before use.
 S23- Do not breathe gas/fumes/vapour/spray.
 S24- Avoid contact with skin.
 S36/37- Wear suitable protective clothing and gloves.
 S45- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
 S61- Avoid release to the environment. Refer to special instructions/safety data sheet.

Hazardous ingredients

Fuel oil, residual
 Fuels, diesel

Supplemental label elements

Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

Not applicable.

Tactile warning of danger

Not applicable.

2.3 Other hazards

Other hazards which do not result in classification

Will cause burns if hot material contacts eyes.
 Will cause burns if hot material contacts skin.
 This material can contain hydrogen sulphide (H₂S), a very toxic and extremely flammable gas. This material may contain significant quantities of polycyclic aromatic hydrocarbons (PCAs), some of which have been shown by experimental studies to induce skin cancer.
 Note: High Pressure Applications
 Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency.
 See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.

SECTION 3: Composition/information on ingredients

Substance/mixture

Mixture

May Contain: Naphthalene, Sulphur or Sulfur, Hydrogen Sulphide (H₂S)

Classification

Product/ingredient name	CAS no.	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Type
Fuel oil, residual	68476-33-5	40 - 100	Carc. Cat. 2; R45 Repr. Cat. 3; R63 Xn; R20, R48/21 R66	Acute Tox. 4, H332 Carc. 1B, H350 Repr. 2, H361d STOT RE 2, H373	[1] [2]
Fuels, diesel	68334-30-5	0 - 60	N; R50/53 Carc. Cat. 3; R40 Xn; R20, R65 Xi; R38 N; R51/53	Aquatic Chronic 1, H410 Acute Tox. 4, H332 Skin Irrit. 2, H315 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1] [2]

See Section 16 for the full text of the R-phrases declared above.

See Section 16 for the full text of the H statements declared above.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

SECTION 3: Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

Hot product - Flood with water to dissipate heat. In the event of any product remaining, do not try to remove it other than by continued irrigation with water. Obtain medical attention immediately.

Cold product - Wash eye thoroughly with copious quantities of water, ensuring eyelids are held open. Obtain medical advice if any pain or redness develops or persists.

Skin contact

Hot Product - Flood skin with cold water to dissipate heat, cover with clean cotton or gauze, obtain medical advice immediately.

Cold Product - Wash contaminated skin with soap and water. Remove contaminated clothing and wash underlying skin as soon as reasonably practicable.

Never use gasoline, kerosene or other solvents to remove product from skin or clothing.

Inhalation

Get medical attention immediately. If inhaled, remove to fresh air. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

EXPOSURE TO HYDROGEN SULPHIDE:

Casualties suffering ill effects as a result of exposure to hydrogen sulphide should be immediately removed to fresh air and medical assistance obtained without delay. If exposure to vapour, mists or fumes causes drowsiness, headache, blurred vision or irritation of the eyes, nose or throat, remove immediately to fresh air. Keep patient warm and at rest. If any symptoms persist obtain medical advice. Unconscious casualties must be placed in the recovery position. Monitor breathing and pulse rate and if breathing has failed, or is deemed inadequate, respiration must be assisted, preferably by the mouth to mouth method. Administer external cardiac massage if necessary. Seek medical attention immediately.

Ingestion

Get medical attention immediately. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects.

Inhalation of hydrogen sulphide may cause central respiratory depression leading to coma and death. It is irritant to the respiratory tract causing chemical pneumonitis and pulmonary oedema. The onset of pulmonary oedema may be delayed for 24 to 48 hours. Treat with oxygen and ventilate as appropriate. Administer broncho-dilators if indicated and consider administration of corticosteroids. Keep casualty under surveillance for 48 hours in case pulmonary oedema develops.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along tissue planes.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

In case of fire, use water fog, foam, dry chemical or carbon dioxide extinguisher or spray.

Unsuitable extinguishing media

Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Product name Residual Marine Fuel (RMA, RMB, RMD, RME, RMF & RMG)

Product code SMI2112

Page: 3/13

Version 1.02 **Date of issue** 6 August 2013

Format Rest of World
(Rest of World)

Language ENGLISH

SECTION 5: Firefighting measures

Hazards from the substance or mixture

Combustible liquid. Avoid spraying directly into storage containers because of the danger of boil-over. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Vapours can form explosive mixtures with air. Vapours are heavier than air and can spread along the ground or float on water surfaces to remote ignition sources. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard. Boil-over is the rapid increase in volume caused by the presence of water in hot product and the subsequent overflow from a tank. This substance will float and can be reignited on surface water.

Hazardous combustion products

Combustion products may include the following:
carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)
sulphur oxides (SO, SO₂, etc.)
Hydrogen Sulphide (H₂S)
other hazardous substances.

5.3 Advice for firefighters

Special precautions for fire-fighters

Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. First move people out of line-of-sight of the scene and away from windows. This material is very toxic to aquatic organisms. Move containers from fire area if this can be done without risk. No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Eliminate all ignition sources. Immediately contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Ensure good ventilation. Put on appropriate personal protective equipment.

This material can contain hydrogen sulphide (H₂S), a very toxic and extremely flammable gas. Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained positive pressure breathing apparatus (SCBA).

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Storage tanks must be positioned within a bunded area.

Spillages in water or at sea:

Depending upon its temperature the product may be liquid, semi-solid or solid. Protect drains from spills and prevent entry of product, since this may result in blockage on cooling. Should blockage occur, notify the appropriate authority immediately. Product less dense than water: In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities. Collect recovered product and other contaminated materials in suitable tanks or containers for recycle, recovery or safe disposal. Product which is denser than water will sink to the bottom, and usually no intervention will be feasible. If possible, collect the product and contaminated materials with mechanical means, and store/dispose of according to relevant regulations. In special situations (to be assessed on case-by-case basis, according to expert judgement and local conditions), excavations of trenches on the bottom to collect the product with sand may be a feasible option.

6.3 Methods and materials for containment and cleaning up

Product name	Residual Marine Fuel (RMA, RMB, RMD, RME, RMF & RMG)	Product code	SMI2112	Page:	4/13
Version	1.02	Date of issue	6 August 2013	Format	Rest of World (Rest of World)
				Language	ENGLISH

SECTION 6: Accidental release measures

Small spill

Eliminate all ignition sources. Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Eliminate all ignition sources. Immediately contact emergency personnel. Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Dike spill area and do not allow product to reach sewage system and surface or ground water. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spill product. Dispose of via a licensed waste disposal contractor.

Depending upon its temperature the product may be liquid, semi-solid or solid. Protect drains from spills and prevent entry of product, since this may result in blockage on cooling. Should blockage occur, notify the appropriate authority immediately.

6.4 Reference to other sections

See Section 1 for emergency contact information.
See Section 5 for firefighting measures.
See Section 8 for information on appropriate personal protective equipment.
See Section 12 for environmental precautions.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Contact with hot product may cause burns. Put on appropriate personal protective equipment. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid contact of spilt material and runoff with soil and surface waterways. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Do not reuse container. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Regular periodic self inspection of the skin is recommended, especially those areas subject to contamination. In the event of any localised changes in appearance or texture of the skin being noticed, medical advice should be sought without delay.

7.2 Conditions for safe storage, including any incompatibilities

Do not enter storage tanks. If entry to vessels is necessary, follow permit to work procedures. Electrical equipment should not be used unless it is intrinsically safe (i.e. will not produce sparks). Entry to any tanks or other confined space requires a full risk assessment and appropriate control measures to be put in place in conformance with appropriate regulations and industry practice on confined space entry. Explosive air/vapour mixtures can occur, particularly in unventilated or confined spaces. If hydrogen sulphide is present, the flammable limits can be from 4.3 to 45.5% by volume and its presence may promote the formation of pyrophoric iron compounds. If product comes into contact with hot surfaces, or leaks occur from pressurised fuel pipes, the vapour or mists generated will create a flammability or explosion hazard. Light hydrocarbon vapours can build up in the headspace of tanks. These can cause flammability/explosion hazards even at temperatures below the normal flash point (note: flash point must not be regarded as a reliable indicator of the potential flammability of vapour in tank headspaces). Tank headspaces should always be regarded as potentially flammable and care should be taken to avoid static electrical discharge and all ignition sources during filling, ullaging and sampling from storage tanks. Product contaminated rags, paper or material used to absorb spillages, represent a fire hazard, and should not be allowed to accumulate. Dispose of safely immediately after use. This material can contain hydrogen sulphide (H₂S), a very toxic and extremely flammable gas. Vapours containing hydrogen sulphide may accumulate during storage or transport and may also be vented during filling of tanks. Hydrogen sulphide has a typical "bad egg" smell but at high concentrations the sense of smell is rapidly lost, therefore do not rely on sense of smell for detecting hydrogen sulphide. Use specially designed measuring instruments for determining its concentration. When the product is pumped (e.g. during filling, discharge or ullaging) and when sampling, there is a risk of static discharge. Ensure equipment used is properly earthed or bonded to the tank structure.

SECTION 7: Handling and storage

Eliminate all ignition sources. Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Separate from oxidising materials. Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Store in a segregated and approved area. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations

See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Fuel oil, residual	ACGIH TLV (United States). TWA: 0.2 mg/m ³ , (Benzene-soluble)
Fuels, diesel	ACGIH TLV (United States). Absorbed through skin. TWA: 100 mg/m ³ , (measured as total hydrocarbons) 8 hours. Issued/ Revised: 1/2007 Form: Inhalable fraction and vapor TWA: 100 mg/m ³ 8 hours. Issued/Revised: 1/2007 Form: Total hydrocarbons
Naphthalene	EU OEL (Europe). TWA: 50 mg/m ³ 8 hours. Issued/Revised: 7/1991 TWA: 10 ppm 8 hours. Issued/Revised: 7/1991
Hydrogen Sulphide	EU OEL (Europe). TWA: 7 mg/m ³ 8 hours. Issued/Revised: 12/2009 TWA: 5 ppm 8 hours. Issued/Revised: 12/2009 STEL: 14 mg/m ³ 15 minutes. Issued/Revised: 12/2009 STEL: 10 ppm 15 minutes. Issued/Revised: 12/2009

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived No Effect Level

Product/ingredient name	Type	Exposure	Value	Population	Effects	
Fuel oil, residual Fuels, diesel	DNEL	Short term Inhalation	15 minutes	4700 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	8 hours TWA	0.065 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	8 hours TWA	0.12 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	24 hours TWA	0.015 mg/kg bw/day	Consumers	Systemic
	DNEL	Short term Inhalation	15 minutes	4300 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	8 hours TWA	2.9 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	8 hours TWA	68 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	15 minutes	2600 mg/m ³	Consumers	Systemic
	DNEL	Long term Dermal	TWA	1.3 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term	24 hours TWA	20 mg/m ³	Consumers	Systemic

SECTION 8: Exposure controls/personal protection

	Inhalation			
--	------------	--	--	--

Predicted No Effect Concentration

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits.
 All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.
 Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

If local exhaust ventilation or other methods of ventilation are not possible or are insufficient, wear suitable respiratory protective devices. Wear suitable respiratory protective devices if there is a risk of exposure limits being exceeded. The choice of suitable respiratory device will depend upon a risk assessment of the workplace environment and the task being carried out. If required, the respiratory device must be certified as safe in defined explosive atmospheres (EX Label). Respiratory protective devices must be checked to ensure they fit correctly each time they are worn. Please consult European standard EN 529 for further guidance on the selection, use, care and maintenance of respiratory protective devices.

Suitable breathing apparatus (independent of ambient atmosphere) must be worn if any of the following situations apply.

- When the workplace atmosphere is considered to be immediately dangerous to life and health.
- When there is a risk of the workplace atmosphere being oxygen deficient.
- When the workplace atmosphere is uncontrolled.
- When the workplace atmosphere is unknown.
- When there is a risk of loss of consciousness or asphyxiation
- When entry into a confined space is required.
- When there is a risk of gases being released that could be a fire or explosion hazard.
- When the concentration of contaminants in the atmosphere exceeds the level of protection (maximum allowed concentration) given by a filtering device
- When the contaminants have a low odour that would not be tasted or smelt by the wearer of a filtering device if the filter became exhausted or saturated.
- When there is a risk of hydrogen sulphide exposure limits being exceeded.

If there is a requirement for the use of a respiratory protective device, but the use of breathing apparatus (independent of ambient atmosphere) is not required, then a suitable filtering device must be worn.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product.

Recommended: Combined filter suitable for gases, vapours and particles (dust, smoke, mist, aerosol). Filter type: AP.

Eye/face protection

Recommended: Chemical splash goggles.

Skin protection

Hand protection



Hot material: to prevent thermal burns wear heat resistant and impervious gauntlets/gloves.
 Cold material: Wear chemical resistant gloves. Recommended: nitrile gloves.
 Protective gloves must give suitable protection against mechanical risks (i.e. abrasion, blade cut and puncture).
 Do not re-use gloves.
 Protective gloves will deteriorate over time due to physical and chemical damage. Inspect and replace gloves on a regular basis.
 The frequency of replacement will depend upon the circumstances of use.

Hot material: to prevent thermal burns wear heat resistant and impervious gauntlets/gloves.
 Cold material: Wear chemical resistant gloves. Recommended: nitrile gloves.

Product name Residual Marine Fuel (RMA, RMB, RMD, RME, RMF & RMG)	Product code SMi2112	Page: 7/13
Version 1.02 Date of issue 6 August 2013	Format Rest of World (Rest of World)	Language ENGLISH

SECTION 8: Exposure controls/personal protection

Skin and body	<p>☑ Cold material: Wear suitable protective clothing. Footwear highly resistant to chemicals. When there is a risk of ignition wear inherently fire resistant protective clothes and gloves. Refer to standard: ISO 11612 When there is a risk of ignition from static electricity, wear anti-static protective clothing. For greatest effectiveness against static electricity, overalls, boots and gloves should all be anti-static. Refer to standard: EN 1149 Cotton or polyester/cotton overalls will only provide protection against light superficial contamination. Work clothing / overalls should be laundered on a regular basis. Laundering of contaminated work clothing should only be done by professional cleaners who have been told about the hazards of the contamination. Always keep contaminated work clothing away from uncontaminated work clothing and uncontaminated personal clothes. When the risk of skin exposure is high (from experience this could apply to the following tasks: cleaning work, maintenance and service, filling and transfer, taking samples and cleaning up spillages) then a chemical protective suit and boots will be required.</p>
Thermal hazards	<p>Hot material: Protection should be provided for exposed areas of the neck and head. Wear suitable protective clothing to protect against heat and brief contact with flame.</p>
Personal protective equipment (Pictograms)	
Environmental exposure controls	<p>Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.</p>

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Colour	Dark Brown. / Black.
Odour	Oily.
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	150 to 750°C (302 to 1382°F)
Pour point	0 to 30 °C
Flash point	Closed cup: >=60°C (>=140°F) [Pensky-Martens.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Lower: 0.5% Upper: 5%
Vapour pressure	<0.133 kPa (<1 mm Hg) at 20°C
Vapour density	>0.9 [Air = 1]
Relative density	Not available.
Density	975 kg/m ³ (0.975 g/cm ³) at 15°C
Solubility(ies)	Not available.
Partition coefficient: n-octanol/ water	Not available.
Auto-ignition temperature	>250°C (>482°F)
Decomposition temperature	Not available.
Viscosity	Kinematic: 10 to 180 mm ² /s (10 to 180 cSt) at 50°C
Explosive properties	Not available.
Oxidising properties	Not available.

9.2 Other information

No additional information.

Product name	Residual Marine Fuel (RMA, RMB, RMD, RME, RMF & RMG)	Product code	SMI2112	Page:	8/13
Version	1.02	Date of issue	6 August 2013	Format	Rest of World (Rest of World)
				Language	ENGLISH

SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous polymerisation will not occur. Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame). Avoid excessive heat.
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on the likely routes of exposure Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Inhalation Harmful by inhalation. Can cause central nervous system (CNS) depression.

Ingestion No known significant effects or critical hazards.

Skin contact Irritating to skin. Will cause burns if hot material contacts skin.

Eye contact May cause eye irritation. Will cause burns if hot material contacts eyes.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

Ingestion Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Skin contact Adverse symptoms may include the following:
irritation
redness

Eye contact Adverse symptoms may include the following:
pain or irritation
watering
redness

Delayed and immediate effects and also chronic effects from short and long term exposure

Inhalation Vapour, mists or fumes may contain polycyclic aromatic hydrocarbons some of which are known to produce skin cancer. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs. Vapour, mist or fume may irritate the nose, mouth and respiratory tract.

Ingestion If swallowed, may irritate the mouth, throat and digestive system. If swallowed, may cause abdominal pain, stomach cramps, nausea, vomiting and diarrhoea.

Skin contact As with all such products containing potentially harmful levels of PCAs, prolonged or repeated skin contact may eventually result in dermatitis or more serious irreversible skin disorders including cancer.

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs. Vapour, mist or fume may cause eye irritation. Exposure to vapour, mist or fume may cause stinging, redness and watering of the eyes.

Potential chronic health effects

General Harmful: danger of serious damage to health by prolonged exposure in contact with skin. Vapour, mists or fumes may contain polycyclic aromatic hydrocarbons some of which are known to produce skin cancer.

Carcinogenicity May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity No known significant effects or critical hazards.

Product name Residual Marine Fuel (RMA, RMB, RMD, RME, RMF & RMG)

Product code SMI2112

Page: 9/13

Version 1.02 **Date of issue** 6 August 2013

Format Rest of World
(Rest of World)

Language ENGLISH

SECTION 11: Toxicological information

Developmental effects	Possible risk of harm to the unborn child.
Fertility effects	No known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Environmental hazards	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
------------------------------	--

12.2 Persistence and degradability

IOPC Persistent / not persistent. oil: Persistent

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc})	Not available.
Mobility	Spillages may penetrate the soil causing ground water contamination. This material may accumulate in sediments.

12.5 Results of PBT and vPvB assessment

PBT	<input checked="" type="checkbox"/> Not applicable.
vPvB	<input checked="" type="checkbox"/> Not applicable.

12.6 Other adverse effects

Other ecological information	This product has a density close to that of water. Spills are unlikely to form a distinct film on the water surface, and may become dispersed as globules if mixed or agitated. If released to water the product may sink.
-------------------------------------	--

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
----------------------------	---

Hazardous waste	Yes.
European waste catalogue (EWC)	

Waste code	Waste designation
13 07 01*	fuel oil and diesel

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging

Methods of disposal	Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations. Recycle, if possible.
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Never weld, solder or braze empty containers. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
Other information	At sea, used or unwanted product should be stored for eventual discharge into port approved waste oil disposal facilities.



Dusts generated during the removal of ash deposits from engine/boiler combustion surfaces or exhaust spaces, will be harmful if inhaled and may cause nausea and eye, nose and throat irritation. Repeated contact may result in serious irreversible disorders. Before working in combustion/exhaust spaces or handling fuel oil ash/dust the area should be thoroughly damped down with water. If this is not possible, wear full breathing apparatus or

Product name	Residual Marine Fuel (RMA, RMB, RMD, RME, RMF & RMG)	Product code	SMI2112	Page:	10/13
Version	1.02	Date of issue	6 August 2013	Format	Rest of World (Rest of World)
				Language	ENGLISH

SECTION 13: Disposal considerations

positive pressure filter sets. Protective clothing must always be worn. When inspecting combustion/exhaust spaces, wear full face dust respirator and protective clothing.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN 3082	UN 9003	UN 3082	UN 3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Heavy fuel oil)	SUBSTANCES WITH A FLASH-POINT ABOVE 60°C AND NOT MORE THAN 100°C. (Heavy fuel oil)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Heavy fuel oil). Marine pollutant	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Heavy fuel oil)
14.3 Transport hazard class(es)	9 	9 	9 	9 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	No.
Additional information	<u>Hazard identification number</u> 90 <u>Tunnel code</u> E	<u>Remarks</u> Table:C.Danger: 9+ (N2,CMR, F or S).	<u>Emergency schedules (EmS)</u> F-A, S-F	-

14.6 Special precautions for user Not available.

ADR/RID Classification code: M6

ADN Classification code: M6

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

For non-fuel uses - "Restricted to Professional Users. Attention - avoid exposure - obtain special instructions before use". Must be marked on packaging.

Other regulations

REACH Status

The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

United States inventory (TSCA 8b)

All components are listed or exempted.

Australia inventory (AICS)

All components are listed or exempted.

Canada inventory

All components are listed or exempted.

China inventory (IECSC)

Not determined.

Japan inventory (ENCS)

Not determined.

Korea inventory (KECI)

Not determined.

SECTION 15: Regulatory information

Philippines inventory (PICCS) Not determined.

15.2 Chemical Safety Assessment Not applicable.

SECTION 16: Other information

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 CSA = Chemical Safety Assessment
 CSR = Chemical Safety Report
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 DPD = Dangerous Preparations Directive [1999/45/EC]
 DSD = Dangerous Substances Directive [67/548/EEC]
 EINECS = European Inventory of Existing Commercial chemical Substances
 ES = Exposure Scenario
 EUH statement = CLP-specific Hazard statement
 EWC = European Waste Catalogue
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 OECD = Organisation for Economic Co-operation and Development
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 RRN = REACH Registration Number
 SADT = Self-Accelerating Decomposition Temperature
 SVHC = Substances of Very High Concern
 STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
 STOT-SE = Specific Target Organ Toxicity - Single Exposure
 TWA = Time weighted average
 UN = United Nations
 UVCB = Complex hydrocarbon substance
 VOC = Volatile Organic Compound
 vPvB = Very Persistent and Very Bioaccumulative

Full text of abbreviated H statements

H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H332 Harmful if inhaled.
 H350 May cause cancer.
 H351 Suspected of causing cancer.
 H361d Suspected of damaging the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Acute Tox. 4, H302	ACUTE TOXICITY: ORAL - Category 4
Acute Tox. 4, H332	ACUTE TOXICITY: INHALATION - Category 4
Aquatic Acute 1, H400	ACUTE AQUATIC HAZARD - Category 1
Aquatic Chronic 1, H410	LONG-TERM AQUATIC HAZARD - Category 1
Aquatic Chronic 2, H411	LONG-TERM AQUATIC HAZARD - Category 2
Asp. Tox. 1, H304	ASPIRATION HAZARD - Category 1
Carc. 1B, H350	CARCINOGENICITY - Category 1B
Carc. 2, H351	CARCINOGENICITY - Category 2
Repr. 2, H361d	TOXIC TO REPRODUCTION [Unborn child] - Category 2
Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION - Category 2
STOT RE 2, H373	SPECIFIC TARGET ORGAN TOXICITY (REPEATED)

SECTION 16: Other information

EXPOSURE) - Category 2

Full text of abbreviated R phrases

R45- May cause cancer.
 R40- Limited evidence of a carcinogenic effect.
 R63- Possible risk of harm to the unborn child.
 R20- Also harmful by inhalation.
 R22- Also harmful if swallowed.
 R48/21- Also harmful: danger of serious damage to health by prolonged exposure in contact with skin.
 R65- Also harmful: may cause lung damage if swallowed.
 R38- Irritating to skin.
 R66- Repeated exposure may cause skin dryness or cracking.
 R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Full text of classifications [DSD/DPD]

Carc. Cat. 2 - Carcinogen category 2
 Carc. Cat. 3 - Carcinogen category 3
 Repr. Cat. 3 - Toxic to reproduction category 3
 Xn - Harmful
 Xi - Irritant
 N - Dangerous for the environment

History

Date of issue/ Date of revision 06/08/2013.
Date of previous issue 06/08/2013.
Prepared by Product Stewardship

 **Indicates information that has changed from previously issued version.**

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.