

SAFETY DATA SHEET


BP Heating Oil



Section 1. Identification

GHS product identifier	BP Heating Oil
Product code	0000003635
SDS no.	0000003635
Historic SDS no.	YSTSX
<u>Relevant identified uses of the substance or mixture and uses advised against</u>	
Use of the substance/ mixture	Fuel for heaters, boilers, and furnaces. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Manufacturer Supplier	BP Australia Pty Ltd Level 17, 717 Bourke Street Docklands, Victoria 3008 ABN 53 004 085 616 www.bp.com.au Technical Helpline Number: 1300 139 700
EMERGENCY TELEPHONE NUMBER	1800 638 556

Section 2. Hazard(s) identification

Classification of the substance or mixture	 LAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY (inhalation) - Category 4 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 ASPIRATION HAZARD - Category 1
---	--

GHS label elements


Hazard pictograms



Signal word


DANGER

Hazard statements


 H227 - Combustible liquid.
H304 - May be fatal if swallowed and enters airways.
H332 - Harmful if inhaled.
H351 - Suspected of causing cancer.
H373 - May cause damage to organs through prolonged or repeated exposure.
(blood, bone marrow, liver, spleen)

Precautionary statements

General

 P102 - Keep out of reach of children.
P101 - If medical advice is needed, have product container or label at hand.

Prevention

 P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear protective gloves. Wear protective clothing. Wear eye or face protection: Recommended: Safety glasses with side shields.. Wear hearing protection.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Product name BP Heating Oil	Product code 0000003635	Page: 1/13	
Version 2	Date of issue 7/20/2023	Format Australia	Language ENGLISH
		(Australia)	(ENGLISH)

Section 2. Hazard(s) identification

Response	P271 - Use only outdoors or in a well-ventilated area. P260 - Do not breathe vapour. P308 + P313 - IF exposed or concerned: Get medical attention. P304 + P340, P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.
Storage	P405 - Store locked up.
Disposal	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	Repeated exposure may cause skin dryness or cracking.
Other hazards which do not result in classification	Repeated exposure may cause skin dryness or cracking.

Section 3. Composition and ingredient information

Substance/mixture	Mixture
Chemical identity	Distillates (petroleum), straight-run middle

Ingredient name	% (w/w)	CAS number
Distillates (petroleum), straight-run middle	≥90	64741-44-2
naphthalene	≤3	91-20-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

The total concentration of ingredients in this product, reported or not in this section, is 100%.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Inhalation	If inhaled, remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Drench contaminated clothing with water before removing. This is necessary to avoid the risk of sparks from static electricity that could ignite contaminated clothing. Contaminated clothing is a fire hazard. Contaminated leather, particularly footwear, must be discarded. Clean shoes thoroughly before reuse. Get medical attention.
Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Aspiration hazard if swallowed. Can enter lungs and cause damage. Get medical attention immediately.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Product name BP Heating Oil	Product code 0000003635	Page: 2/13	
Version 2	Date of issue 7/20/2023	Format Australia	Language ENGLISH
		(Australia)	(ENGLISH)

Section 4. First aid measures

Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects. Product can be aspirated on swallowing or following regurgitation of stomach contents, and can cause severe and potentially fatal chemical pneumonitis, which will require urgent treatment. Because of the risk of aspiration, induction of vomiting and gastric lavage should be avoided. Gastric lavage should be undertaken only after endotracheal intubation. Monitor for cardiac dysrhythmias.

Specific treatments

No specific treatment.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media

In case of fire, use water fog, foam, dry chemical or carbon dioxide extinguisher or spray.

Unsuitable extinguishing media

Do not use water jet.

Specific hazards arising from the chemical

Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Vapours can form explosive mixtures with air. Vapours are heavier than air and can spread along the ground or float on water surfaces to remote ignition sources. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Liquid will float and may reignite on surface of water.

Hazardous thermal decomposition products

Combustion products may include the following:
carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Immediately contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling. Eliminate all ignition sources.

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Section 6. Accidental release measures

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities. Collect recovered product and other contaminated materials in suitable tanks or containers for recycle, recovery or safe disposal.

Methods and material for containment and cleaning up

Small spill

Eliminate all ignition sources. Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. The method and equipment used must be in conformance with appropriate regulations and industry practice on explosive atmospheres.

Large spill

Eliminate all ignition sources. Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Dike spill area and do not allow product to reach sewage system and surface or ground water. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilt product. The method and equipment used must be in conformance with appropriate regulations and industry practice on explosive atmospheres. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not swallow. Aspiration hazard if swallowed. Can enter lungs and cause damage. Never siphon by mouth. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Section 7. Handling and storage

Light hydrocarbon vapours can build up in the headspace of tanks. These can cause flammability/explosion hazards even at temperatures below the normal flash point (note: flash point must not be regarded as a reliable indicator of the potential flammability of vapour in tank headspaces). Tank headspaces should always be regarded as potentially flammable and care should be taken to avoid static electrical discharge and all ignition sources during filling, ullaging and sampling from storage tanks. Do not enter storage tanks. If entry to vessels is necessary, follow permit to work procedures. Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. When the product is pumped (e.g. during filling, discharge or ullaging) and when sampling, there is a risk of static discharge. Ensure equipment used is properly earthed or bonded to the tank structure. Electrical equipment should not be used unless it is intrinsically safe (i.e. will not produce sparks). Explosive air/vapour mixtures may form at ambient temperature. If product comes into contact with hot surfaces, or leaks occur from pressurised fuel pipes, the vapour or mists generated will create a flammability or explosion hazard. Product contaminated rags, paper or material used to absorb spillages, represent a fire hazard, and should not be allowed to accumulate. Dispose of safely immediately after use.

Section 8. Exposure controls and personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
<input checked="" type="checkbox"/> Distillates (petroleum), straight-run middle naphthalene	ACGIH TLV (United States). TWA: 5 mg/m ³ 8 hours. Form: Oil mist, mineral Safe Work Australia (Australia). STEL: 79 mg/m ³ 15 minutes. Issued/Revised: 4/2013 STEL: 15 ppm 15 minutes. Issued/Revised: 4/2013 TWA: 52 mg/m ³ 8 hours. Issued/Revised: 4/2013 TWA: 10 ppm 8 hours. Issued/Revised: 4/2013

Biological exposure indices

No exposure indices known.

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Product name BP Heating Oil

Product code 0000003635

Page: 5/13

Version 2

Date of issue 7/20/2023

Format Australia

Language ENGLISH

(Australia)

(ENGLISH)

Section 8. Exposure controls and personal protection

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Recommended: Safety glasses with side shields.

Skin protection

Hand protection

Wear chemical resistant gloves.

Do not re-use gloves. Protective gloves must give suitable protection against mechanical risks (i.e. abrasion, blade cut and puncture). Protective gloves will deteriorate over time due to physical and chemical damage. Inspect and replace gloves on a regular basis. The frequency of replacement will depend upon the circumstances of use.

Recommended: Nitrile gloves.

Skin protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Wear suitable protective clothing.

Footwear highly resistant to chemicals.

When there is a risk of ignition wear inherently fire resistant protective clothes and gloves.

When there is a risk of ignition from static electricity, wear anti-static protective clothing. For greatest effectiveness against static electricity, overalls, boots and gloves should all be anti-static.

When the risk of skin exposure is high (from experience this could apply to the following tasks: cleaning work, maintenance and service, filling and transfer, taking samples and cleaning up spillages) then a chemical protective suit and boots will be required.

Work clothing / overalls should be laundered on a regular basis. Laundering of contaminated work clothing should only be done by professional cleaners who have been told about the hazards of the contamination. Always keep contaminated work clothing away from uncontaminated work clothing and uncontaminated personal clothes.

Recommended: Avoid contact with skin and clothing. Wear suitable protective clothing.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Use with adequate ventilation.

If there is a requirement for the use of a respiratory protective device, but the use of breathing apparatus (independent of ambient atmosphere) is not required, then a suitable filtering device must be worn.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product.

Recommended: Approved/certified respirator with organic vapour and particulate filters.

Refer to standards:

Respiratory protection:AS/NZS 1715 and AS/NZS 1716

Gloves:AS/NZS 2161.1

Eye protection:AS/NZS 1336 and AS/NZS 1337

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	Liquid.
Colour	Clear. Water White.
Odour	Hydrocarbon.
Odour threshold	Not available.
pH	Not available.
Melting point	Not available.
Boiling point, initial boiling point, and boiling range	150 to 280°C (302 to 536°F)
Flash point	Closed cup: >61.5°C (>142.7°F) [Pensky-Martens]
Evaporation rate	Not available. Not applicable. Based on - Physical state
Lower and upper explosion limit/flammability limit	Lower: 0.7% Upper: 5%
Vapour pressure	<0.1 kPa (<0.7501 mm Hg)
Relative vapour density	>1 [Air = 1]
Relative density	1
Density	810 to 830 kg/m ³ (0.81 to 0.83 g/cm ³) at 15°C
Solubility(ies)	

Media	Result
Water	Not soluble

Solubility in water Not available.

Miscible with water No.

Partition coefficient: n-octanol/water Not applicable.

Auto-ignition temperature

Ingredient name	°C	°F	Method
Distillates (petroleum), straight-run middle	240	464	
naphthalene	526 to 587	978.8 to 1088.6	DIN 51794

Decomposition temperature Not available.

Viscosity Kinematic: 1.2 to 2.1 mm²/s (1.2 to 2.1 cSt) at 40°C

Remarks Vapour pressure: Reid <1 kPa

Particle characteristics

Median particle size Not applicable.

Section 10. Stability and reactivity

Reactivity No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

Chemical stability The product is stable.

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will not occur.
Under normal conditions of storage and use, hazardous polymerisation will not occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame). Avoid excessive heat.

Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Product name BP Heating Oil

Product code 0000003635

Page: 7/13

Version 2 Date of issue 7/20/2023

Format Australia

Language ENGLISH

(Australia)

(ENGLISH)

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), straight-run middle	LC50 Inhalation Dusts and mists	Rat	>2.53 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
naphthalene	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Dermal	Rabbit	20 g/kg	-
	LD50 Oral	Rat	490 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Distillates (petroleum), straight-run middle	Eyes - Non-irritating to the eyes.	Rabbit	-	-	-
	Skin - Non-irritant to skin.	Rabbit	-	-	-

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
Distillates (petroleum), straight-run middle	skin	Guinea pig	Not sensitising

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Distillates (petroleum), straight-run middle	Equivalent to OECD 476	Experiment: In vitro Subject: Mammal - species unspecified Cell: Somatic	Positive
	Equivalent to OECD 471	Experiment: In vitro Subject: Non-mammalian species Cell: Somatic	Positive
	Equivalent to OECD 479	Experiment: In vitro Subject: Non-mammalian species Cell: Somatic	Negative
	Equivalent to OECD 475	Experiment: In vivo Subject: Non-mammalian species Cell: Somatic	Negative
		Subject: Mammal - species unspecified Cell: Germ	

Conclusion/Summary

Not classified. Based on available data, the classification criteria are not met.

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), straight-run middle	Positive - Dermal - Unspecified	Mouse	-	2 years

Conclusion/Summary

Not classified. Based on available data, the classification criteria are not met. Mechanistic understanding suggests tumors observed in animal models are not relevant to man.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
Distillates (petroleum), straight-run middle	-	-	Negative	Rat	Dermal	23 days
	-	Negative	-	Rat	Dermal	27 days

Product name BP Heating Oil

Product code 0000003635

Page: 8/13

Version 2 Date of issue 7/20/2023

Format Australia

Language ENGLISH

(Australia)

(ENGLISH)

Section 11. Toxicological information

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Distillates (petroleum), straight-run middle	Category 2	Not determined	blood, bone marrow, liver and spleen

Aspiration hazard

Name	Result
Distillates (petroleum), straight-run middle	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact	No known significant effects or critical hazards.
Inhalation	Harmful if inhaled.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.
Ingestion	Aspiration hazard if swallowed -- harmful or fatal if liquid is aspirated into lungs.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	No specific data.
Inhalation	Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	Adverse symptoms may include the following: irritation dryness cracking
Ingestion	Adverse symptoms may include the following: nausea or vomiting

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact	Vapour, mist or fume may cause eye irritation. Exposure to vapour, mist or fume may cause stinging, redness and watering of the eyes.
Inhalation	Vapour, mist or fume may irritate the nose, mouth and respiratory tract.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea. If swallowed, may irritate the mouth, throat and digestive system. If swallowed, may cause abdominal pain, stomach cramps, nausea, vomiting, diarrhoea, dizziness and drowsiness.
General	May cause damage to organs through prolonged or repeated exposure.
Carcinogenicity	<input checked="" type="checkbox"/> Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

Numerical measures of toxicity

Product name BP Heating Oil	Product code 0000003635	Page: 9/13	
Version 2	Date of issue 7/20/2023	Format Australia	Language ENGLISH
		(Australia)	(ENGLISH)

Section 11. Toxicological information

Acute toxicity estimates

Route

Oral
Inhalation (dusts and mists)

ATE value

24990 mg/kg
1.5 mg/l

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
<input checked="" type="checkbox"/> Distillates (petroleum), straight-run middle	EL50 >1000 mg/l Fresh water	Micro-organism	40 hours
	NOEL 3.099 mg/l Fresh water	Micro-organism	40 hours
	Acute EL50 22 mg/l Nominal Fresh water	Algae	72 hours
	Acute EL50 2.079 mg/l Nominal Fresh water	Algae	72 hours
	Acute EL50 210 mg/l Nominal Fresh water	Daphnia	48 hours
	Acute EL50 9.983 mg/l Nominal Fresh water	Daphnia	48 hours
	Acute EL50 68 mg/l Nominal Fresh water	Daphnia	48 hours
	Acute EbL50 25 mg/l Nominal Fresh water	Algae	72 hours
	Acute EbL50 10 mg/l Nominal Fresh water	Algae	72 hours
	Acute ErL50 78 mg/l Nominal Fresh water	Algae	72 hours
	Acute ErL50 22 mg/l Nominal Fresh water	Algae	72 hours
	Acute LL50 65 mg/l Nominal Fresh water	Fish	96 hours
	Acute LL50 1.301 mg/l Fresh water	Fish	96 hours
	Acute LL50 21 mg/l Nominal Fresh water	Fish	96 hours
	Acute NOEL 46 mg/l Nominal Fresh water	Daphnia	48 hours
	Acute NOEL 46 mg/l Nominal Fresh water	Daphnia	48 hours
	Acute NOEL 10 mg/l Fresh water	Fish	96 hours
	Chronic NOEL 10 mg/l Nominal Fresh water	Algae	72 hours
	Chronic NOEL <1 mg/l Nominal Fresh water	Algae	72 hours
	Chronic NOEL 0.167 mg/l Nominal Fresh water	Daphnia	21 days
naphthalene	Chronic NOEL 0.068 mg/l Fresh water	Fish	14 days
	EC50 0.4 mg/l	Algae	96 hours
	EC50 2.16 mg/l	Crustaceans	48 hours

Conclusion/Summary

Toxic to aquatic life with long lasting effects.

Persistence and degradability

Readily biodegradable

Product/ingredient name	Test	Result	Dose	Inoculum
-------------------------	------	--------	------	----------

Product name BP Heating Oil

Product code 0000003635

Page: 10/13

Version 2 Date of issue 7/20/2023

Format Australia
(Australia)

Language ENGLISH
(ENGLISH)

Section 12. Ecological information

Distillates (petroleum), straight-run middle	OECD 301F	57.5 % - Not readily - 28 days		-
	OECD 301F	60 % - Readily - 28 days	mg/l	-
	EPA OTS	35 % - Not readily - 28 days	mg/l	-
	796.3100			
	aerobic aquatic biodegradation			

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogP _{ow}	BCF	Potential
naphthalene	3.4	-	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) Not available.

Mobility Spillages may penetrate the soil causing ground water contamination. This material may accumulate in sediments.

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal considerations



Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Special Precautions for Landfill or Incineration

No additional special precautions identified.

Section 14. Transport information

	ADG	IMDG	IATA
UN number	Not regulated.	UN1202	UN1202
UN proper shipping name	-	GAS OIL. Marine pollutant	GAS OIL
Transport hazard class(es)	-	3 	3 
Packing group	-	III	III

Product name BP Heating Oil

Product code 0000003635

Page: 11/13

Version 2 Date of issue 7/20/2023

Format Australia

Language ENGLISH

(Australia)

(ENGLISH)

Section 14. Transport information

Environmental hazards	No.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Additional information	Remarks Combustible liquid Class C1 (AS 1940).	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Emergency schedules F-E, S-E	The environmentally hazardous substance mark may appear if required by other transportation regulations.

Special precautions for user Not available.

Transport in bulk according to IMO instruments **Proper shipping name** MARPOL Annex 1 rules apply for bulk shipments by sea.
Category: gas oils, including ship's bunkers

Section 15. Regulatory information

Standard for the Uniform Scheduling of Medicines and Poisons

Not scheduled - When packed in containers having capacity of greater than 20 litres.
S5 - When packed in containers having capacity of less than 20 litres.

Consumer products - This product is exempt per Appendix A of the SUSMP.

Industrial Products - Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with NOSHC National Code of Practice for labelling of workplace substances.

Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

International lists

National inventory

REACH Status

For the REACH status of this product please consult your company contact, as identified in Section 1.

Australia inventory (AIC)

All components are listed or exempted.

Canada inventory

All components are listed or exempted.

China inventory (IECSC)

All components are listed or exempted.

Japan inventory (CSCL)

Not determined.

Korea inventory (KECI)

All components are listed or exempted.

Philippines inventory (PICCS)

All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI)

All components are listed or exempted.

United States inventory (TSCA 8b)

All components are active or exempted.

Product name BP Heating Oil

Product code 0000003635 **Page:** 12/13

Version 2 **Date of issue** 7/20/2023

Format Australia

Language ENGLISH

(Australia)

(ENGLISH)

Section 16. Any other relevant information

History

Date of printing 7/20/2023

Date of issue/Date of revision 7/20/2023

Date of previous issue 12/6/2018

Version 2

Prepared by Product Stewardship

Key to abbreviations

ADG = Australian Dangerous Goods

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

NOHSC = National Occupational Health and Safety Commission

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]

STEL = Short term exposure limit

SUSMP = Standard Uniform Schedule of Medicine and Poisons

UN = United Nations

TWA = Time weighted average

VOC = Volatile Organic Compound

SADT = Self-Accelerating Decomposition Temperature

Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 4	On basis of test data
ACUTE TOXICITY (inhalation) - Category 4	Expert judgment
CARCINOGENICITY - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2	Expert judgment
ASPIRATION HAZARD - Category 1	Expert judgment

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name BP Heating Oil

Product code 0000003635

Page: 13/13

Version 2

Date of issue 7/20/2023

Format Australia

Language ENGLISH

(Australia)

(ENGLISH)