

# SAFETY DATA SHEET












BP Premium Propane

## Section 1. Identification

<b>GHS product identifier</b>	BP Premium Propane
<b>Product code</b>	0000003181
<b>SDS no.</b>	0000003181
<b>Historic SDS no.</b>	ACPWL
<b>Relevant identified uses of the substance or mixture and uses advised against</b>	
<b>Use of the substance/ mixture</b>	Multi-purpose product with applications including gaseous fuel for domestic, commercial and industrial uses; internal combustion engine fuel; aerosol propellant; Chemical feedstock.
<b>Manufacturer Supplier</b>	BP Australia Pty Ltd Level 17, 717 Bourke Street Docklands, Victoria 3008 ABN 53 004 085 616  www.bp.com.au  Technical Helpline Number: 1300 139 700
<b>EMERGENCY TELEPHONE NUMBER</b>	1800 638 556

## Section 2. Hazard(s) identification

<b>Classification of the substance or mixture</b>	 LAMMABLE GASES - Category 1 GASES UNDER PRESSURE - Liquefied gas
<b>GHS label elements</b>	
<b>Hazard pictograms</b>	 
<b>Signal word</b>	DANGER
<b>Hazard statements</b>	 H220 - Extremely flammable gas. H280 - Contains gas under pressure; may explode if heated.
<b>Precautionary statements</b>	
<b>General</b>	 P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
<b>Prevention</b>	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>Response</b>	 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely. P381 - In case of leakage, eliminate all ignition sources.
<b>Storage</b>	 P410 + P403 - Protect from sunlight. Store in a well-ventilated place.
<b>Disposal</b>	 Not applicable.
<b>Supplemental label elements</b>	Keep container tightly closed. Use only with adequate ventilation. Do not enter storage areas and confined spaces unless adequately ventilated.

<b>Product name</b> BP Premium Propane	<b>Product code</b> 0000003181	<b>Page:</b> 1/11
<b>Version</b> 2	<b>Date of issue</b> 4/22/2021	<b>Format</b> Australia
	<b>(Australia)</b>	<b>Language</b> ENGLISH <b>(ENGLISH)</b>

## Section 2. Hazard(s) identification

### Other hazards which do not result in classification

Acts as a simple asphyxiant.

At very high concentrations, can displace the normal air and cause suffocation from lack of oxygen.

Liquid can cause burns similar to frostbite.

## Section 3. Composition and ingredient information

### Substance/mixture

Mixture

Petroleum gas. A small quantity (typically up to 50 ppm) of ethyl mercaptan (stenching agent) is commonly added to assist in leak detection.

Contains <0.10% 1,3-butadiene.

Ingredient name	% (v/v)	CAS number
Propane	≥40	74-98-6
propylene	≤60	115-07-1
Butane	<7.5	106-97-8
Ethane	≤5	74-84-0
Pentane	≤3	109-66-0

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

#### Eye contact

Contact with liquid: Immediately flush with plenty of tepid water (105-115° F; 41-46° C). DO NOT USE HOT WATER. Get immediate medical attention.

#### Inhalation

Inhaled, remove to fresh air. Get medical attention if symptoms occur.

#### Skin contact

Contact with liquid: Immediately flush with plenty of tepid water (105-115° F; 41-46° C). DO NOT USE HOT WATER. Get immediate medical attention.

Do not use hot water. Flush contaminated skin with plenty of water. Drench contaminated clothing with water before removing. This is necessary to avoid the risk of sparks from static electricity that could ignite contaminated clothing. Contaminated clothing is a fire hazard. Contaminated leather, particularly footwear, must be discarded. Remove contaminated clothing and shoes. Clean shoes thoroughly before reuse. In case of contact with liquid, warm frozen tissues slowly with lukewarm water and get medical attention. Get medical attention if symptoms occur. Do not apply ointment or powders. DO NOT rub or compress the burnt area of skin. DO NOT attempt to remove portions of clothing glued to the skin, but cut round them.

#### Ingestion

Not applicable (gas).

### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### Indication of immediate medical attention and special treatment needed, if necessary

#### Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects. Treat cold burns as frostbite.

#### Specific treatments

No specific treatment.

#### Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

## Section 5. Firefighting measures

### Extinguishing media

#### Suitable extinguishing media

If gas has ignited, do not attempt to extinguish but stop gas flow and allow to burn out. Use water spray to cool heat-exposed containers, and to protect surrounding areas and personnel effecting shut-off.

#### Unsuitable extinguishing media

Do not use water jet.

### Specific hazards arising from the chemical

☑ Contains gas under pressure. Extremely flammable gas. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapour/gas is heavier than air and will spread along the ground.

### Hazardous thermal decomposition products

☑ Combustion products may include the following:  
carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

### Special protective actions for fire-fighters

☑ No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. If involved in fire, shut off flow immediately if it can be done without risk. If this is impossible, withdraw from area and allow fire to burn. Fight fire from protected location or maximum possible distance. Eliminate all ignition sources if safe to do so. In case of fire, allow gas to burn if flow cannot be shut off immediately. Apply water from a safe distance to cool container and protect surrounding areas. Every precaution must be taken to keep containers cool to avoid the possibility of a boiling liquid expanding vapour explosion (BLEVE). Pressurised containers are liable to explode violently when subjected to high temperatures.

### Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear. For incidents involving large quantities, thermally insulated undergarments and thick textile or leather gloves should be worn.

### Hazchem code

2YE

### Remark

May form explosive mixtures with air.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

☑ Immediately contact emergency personnel. Accidental releases pose a serious fire or explosion hazard. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. No flares, smoking or flames in hazard area. Avoid breathing gas. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling. Eliminate all ignition sources.

#### For emergency responders

Do not enter a vapour cloud except for rescue; self-contained breathing apparatus must be worn. A gas detector or instrument to detect explosive atmospheres (explosimeter) can be used to check for combustible gas or vapour in an atmosphere, but it needs care and training to be used safely. Use suitable protective equipment. Liquid leaks generate large volumes of extremely flammable gas. See also the information in "For non-emergency personnel".

### Environmental precautions

Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

**Product name** BP Premium Propane

**Product code** 000003181

**Page:** 3/11

**Version** 2

**Date of issue** 4/22/2021

**Format** Australia

**Language** ENGLISH

(Australia)

(ENGLISH)

## Section 6. Accidental release measures

### Small spill

Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment.

### Large spill

Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. The method and equipment used must be in conformance with appropriate regulations and industry practice on explosive atmospheres.

## Section 7. Handling and storage

### Precautions for safe handling

#### Protective measures

Put on appropriate personal protective equipment (see Section 8). Contains gas under pressure. Do not get in eyes or on skin or clothing. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not puncture or incinerate container.

#### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Eliminate all ignition sources. Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use.

## Section 8. Exposure controls and personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
Propane	<b>ACGIH TLV (United States). Oxygen Depletion [Asphyxiant]. Explosive potential.</b>
propylene	<b>ACGIH TLV (United States).</b> TWA: 500 ppm 8 hours. Issued/Revised: 12/2005
Butane	<b>Safe Work Australia (Australia).</b> TWA: 1900 mg/m <sup>3</sup> 8 hours. Issued/Revised: 5/1995 TWA: 800 ppm 8 hours. Issued/Revised: 5/1995
Ethane	<b>ACGIH TLV (United States). Oxygen Depletion [Asphyxiant]. Explosive potential.</b>
Pentane	<b>Safe Work Australia (Australia).</b> STEL: 2210 mg/m <sup>3</sup> 15 minutes. Issued/Revised: 5/1995 STEL: 750 ppm 15 minutes. Issued/Revised: 5/1995 TWA: 1770 mg/m <sup>3</sup> 8 hours. Issued/Revised: 5/1995 TWA: 600 ppm 8 hours. Issued/Revised: 5/1995

## Section 8. Exposure controls and personal protection

### Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

☑ Safety glasses with side shields. If there is a risk of liquid release or vapour pressure jets (e.g. during filling operations) wear a full face visor, chemical goggles and helmet to prevent cold burns / frostbite.

#### Skin protection

##### Hand protection

☑ Wear suitable gloves. To prevent cold burns and frostbite wear cold resistant and impervious gauntlets/gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/ manufacturer and with a full assessment of the working conditions.

##### Skin protection

☑ Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When handling cylinders wear protective footwear and suitable gloves. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

##### Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

##### Respiratory protection

Use with adequate ventilation.  
Ensure good ventilation.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Approved air-supplied breathing apparatus must be worn where there is a risk of oxygen deficiency (i.e. low oxygen concentration).  
Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn.  
Air-filtering respirators, also called air-purifying respirators, will not be adequate

## Section 8. Exposure controls and personal protection

under conditions of oxygen deficiency (i.e. low oxygen concentration), and would not be considered suitable where airborne concentrations of chemicals with a significant hazard are present. In these cases air-supplied breathing apparatus will be required. If there is a requirement for the use of a respiratory protective device, but the use of breathing apparatus (independent of ambient atmosphere) is not required, then a suitable filtering device must be worn.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

### Thermal hazards

If there is a risk of contact with the liquid, all protective equipment worn should be suitable for use with extremely low temperature materials.

### Refer to standards:

Respiratory protection:AS/NZS 1715 and AS/NZS 1716

Gloves:AS/NZS 2161.1

Eye protection:AS/NZS 1336 and AS/NZS 1337

## Section 9. Physical and chemical properties

### Appearance

Physical state	Liquefied gas.
Colour	Colourless.
Odour	Sulphurous. / Distinctive when stenchd
Odour threshold	0.001 ppm Based on Ethyl mercaptan
pH	Not applicable. Based on Solubility in Water (Very slightly soluble in water)
Melting point	-187.6°C (-305.7°F)
Boiling point	-45°C (-49°F)
Flash point	Closed cup: -105°C (-157°F) [Pensky-Martens.]
Evaporation rate	Not applicable (gas).
Flammability (solid, gas)	Extremely flammable
Lower and upper explosive (flammable) limits	Lower: 2.2% Upper: 9.5%
Vapour pressure	799.9 to 1530 kPa (6000 to 11476 mm Hg) [40°C (104°F)]
Vapour density	1 [Air = 1]
Relative density	1
Density	520 kg/m <sup>3</sup> (0.52 g/cm <sup>3</sup> ) at 15°C
Solubility	Very slightly soluble in water
Partition coefficient: n-octanol/water	1.09 Based on Propane.
Auto-ignition temperature	287°C (548.6°F)
Decomposition temperature	Not available.
Viscosity	Not applicable. Based on physical state.

## Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.

Product name BP Premium Propane

Product code 0000003181

Page: 6/11

Version 2 Date of issue 4/22/2021

Format Australia

Language ENGLISH

(Australia)

(ENGLISH)



## Section 10. Stability and reactivity

<b>Conditions to avoid</b>	Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow gas to accumulate in low or confined areas.
<b>Incompatible materials</b>	Reactive or incompatible with the following materials: oxidising materials.
<b>Hazardous decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Propane	LC50 Inhalation Gas.	Rat	>800000 ppm	15 minutes

**Conclusion/Summary** Not classified. Based on available data, the classification criteria are not met.

#### Mutagenicity

Product/ingredient name	Test	Experiment	Result
Propane	OECD 471	Experiment: In vitro Subject: Non-mammalian species	Negative
	OECD 474	Experiment: In vivo Subject: Unspecified Cell: Somatic	Negative

**Conclusion/Summary** Not classified. Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
Propane	-	-	Negative	Rat	Inhalation	14 days
	-	Negative	Negative	Rat	Inhalation	42 days
	-	Negative	-	Rat	Inhalation	90 days

**Conclusion/Summary** Not classified. Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Pentane	Category 3	-	Narcotic effects

**Information on likely routes of exposure** Routes of entry anticipated: Dermal, Inhalation.

#### Potential acute health effects

##### Eye contact

Liquid can cause burns similar to frostbite.

##### Inhalation

At very high concentrations, can displace the normal air and cause suffocation from lack of oxygen. High vapour concentrations may produce symptoms of oxygen deficiency which, coupled with central nervous system depression, may lead to rapid loss of consciousness.

##### Skin contact

Dermal contact with rapidly evaporating liquid could result in freezing of the tissues or frostbite.

##### Ingestion

Ingestion of liquid can cause burns similar to frostbite.

#### Symptoms related to the physical, chemical and toxicological characteristics

##### Eye contact

Adverse symptoms may include the following:  
frostbite

## Section 11. Toxicological information

<b>Inhalation</b>	Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
<b>Skin contact</b>	Adverse symptoms may include the following: frostbite
<b>Ingestion</b>	Adverse symptoms may include the following: frostbite

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Ingestion</b>	<input checked="" type="checkbox"/> Ingestion of large quantities may cause nausea and diarrhoea.
<b>General</b>	<input checked="" type="checkbox"/> No known significant effects or critical hazards.
<b>Carcinogenicity</b>	No known significant effects or critical hazards.
<b>Mutagenicity</b>	No known significant effects or critical hazards.
<b>Teratogenicity</b>	No known significant effects or critical hazards.
<b>Developmental effects</b>	No known significant effects or critical hazards.
<b>Fertility effects</b>	No known significant effects or critical hazards.

### **Other information**

This material is an asphyxiant. Asphyxiants may reduce the oxygen concentration in the air to dangerous levels. Symptoms of lack of oxygen include increased depth and frequency of breathing, air hunger, dizziness, headache, nausea or loss of consciousness.

High vapour concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. Exposure to vapour at high concentrations may have the following effects: heartbeat irregularity (arrhythmia)

## Section 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
<input checked="" type="checkbox"/> Propane	Acute EC50 11.89 mg/l	Algae	96 hours
	Acute LC50 27.14 mg/l	Daphnia	48 hours
	Acute LC50 49.9 mg/l	Fish	96 hours

### Persistence and degradability

Expected to be biodegradable.

Product/ingredient name	Test	Result	Dose	Inoculum
<input checked="" type="checkbox"/> Propane	Modelled data	50 % - Readily - 3 days	-	-

### Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
<input checked="" type="checkbox"/> Propane	1.09	-	low
propylene	1.77	-	low
Butane	2.89	-	low
Ethane	1.09	-	low
Pentane	3.45	-	low

**Product name** BP Premium Propane

**Product code** 0000003181

**Page:** 8/11

**Version** 2 **Date of issue** 4/22/2021

**Format** Australia

**Language** ENGLISH

(Australia)

(ENGLISH)



## Section 12. Ecological information

### Mobility in soil

Soil/water partition coefficient ( $K_{oc}$ )

Not available.

Mobility

Spillages are unlikely to penetrate the soil. This product is likely to volatilise rapidly into the air because of its high vapour pressure.

### Other ecological information

Unlikely to cause long term effects in the aquatic environment.

## Section 13. Disposal considerations




### Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Empty pressure vessels should be returned to the supplier. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

### Special Precautions for Landfill or Incineration

No additional special precautions identified.

## Section 14. Transport information

	ADG	IMDG	IATA
UN number	UN1978	UN1978	UN1978
UN proper shipping name	PROPANE	PROPANE	Propane
Transport hazard class(es)	2.1 	2.1 	2.1 
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information	<u>Hazchem code</u> 2YE <u>Initial emergency response guide</u> 04	<u>Emergency schedules</u> F-D, S-U	<u>Quantity limitation</u> Passenger and Cargo Aircraft: Forbidden. Cargo Aircraft Only: 150 kg. Limited Quantities - Passenger Aircraft: Forbidden.

### Special precautions for user

No known special precautions required. See Section: "Handling and storage" for additional information.

Product name BP Premium Propane

Product code 0000003181

Page: 9/11

Version 2

Date of issue 4/22/2021

Format Australia

Language ENGLISH

(Australia)

(ENGLISH)

## Section 15. Regulatory information

### Standard for the Uniform Scheduling of Medicines and Poisons

Not regulated.

### Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

#### Montreal Protocol

Ingredient name	List name	Status
Not listed.		

#### Stockholm Convention on Persistent Organic Pollutants

Ingredient name	List name	Status
Not listed.		

#### Rotterdam Convention on Prior Informed Consent (PIC)

Ingredient name	List name	Status
Not listed.		

### International lists

#### National inventory

##### REACH Status

For the REACH status of this product please consult your company contact, as identified in Section 1.

##### Australia inventory (AICS)

Contact supplier for regulatory information.

##### Canada inventory

Not determined.

##### China inventory (IECSC)

Not determined.

##### Japan inventory (ENCS)

Not determined.

##### Korea inventory (KECI)

Not determined.

##### Philippines inventory (PICCS)

Not determined.

##### Taiwan Chemical Substances Inventory (TCSI)

Not determined.

##### United States inventory (TSCA 8b)

Not determined.

## Section 16. Any other relevant information

### History

Date of printing 4/22/2021

Date of issue/Date of revision 4/22/2021

Date of previous issue 1/29/2016

Version 2

Prepared by Product Stewardship

### Key to abbreviations

ADG = Australian Dangerous Goods

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

Product name BP Premium Propane

Product code 0000003181

Page: 10/11

Version 2 Date of issue 4/22/2021

Format Australia

Language ENGLISH


(Australia)

(ENGLISH)

## Section 16. Any other relevant information

NOHSC = National Occupational Health and Safety Commission  
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]  
STEL = Short term exposure limit  
SUSMP = Standard Uniform Schedule of Medicine and Poisons  
UN = United Nations  
TWA = Time weighted average  
VOC = Volatile Organic Compound  
SADT = Self-Accelerating Decomposition Temperature  
Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

### Procedure used to derive the classification

Classification	Justification
 FLAMMABLE GASES - Category 1 GASES UNDER PRESSURE - Liquefied gas	On basis of test data On basis of test data

 Indicates information that has changed from previously issued version.

### Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.