

SAFETY DATA SHEET



Ethanol Denatured Fuel Grade

Section 1. Identification

GHS product identifier	Ethanol Denatured Fuel Grade
Product code	0000002719
SDS no.	0000002719
Relevant identified uses of the substance or mixture and uses advised against	
Use of the substance/ mixture	Fuel. This product is for industrial use only. Denaturants have been added to this product and it is unfit for human consumption.
Manufacturer Supplier	BP Australia Pty Ltd Level 17, 717 Bourke Street Docklands, Victoria 3008 ABN 53 004 085 616 www.bp.com.au Technical Helpline Number: 1300 139 700
EMERGENCY TELEPHONE NUMBER	1800 638 556

Section 2. Hazard(s) identification

Classification of the substance or mixture	FLAMMABLE LIQUIDS - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A
---	---

GHS label elements

Hazard pictograms



Signal word	DANGER
Hazard statements	H225 - Highly flammable liquid and vapour. H319 - Causes serious eye irritation.

Precautionary statements

Prevention

P280 - Wear protective gloves, protective clothing and eye or face protection.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 - Use explosion-proof electrical, ventilating or lighting equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P233 - Keep container tightly closed.
P264 - Wash hands thoroughly after handling.

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical attention.

Storage

P403 + P235 - Store in a well-ventilated place. Keep cool.

Disposal

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Product name Ethanol Denatured Fuel Grade	Product code 0000002719	Page: 1/13	
Version 2	Date of issue 4/28/2021	Format Australia	Language ENGLISH
		(Australia)	(ENGLISH)

Section 2. Hazard(s) identification

Supplemental label elements Not applicable.

Other hazards which do not result in classification None known.

Section 3. Composition and ingredient information

Substance/mixture Mixture

Mixture of: Ethanol and Gasoline

Gasoline: A complex mixture of volatile hydrocarbons containing paraffins, naphthenes, olefins and aromatics with carbon numbers predominantly between C4 and C12. May contain oxygenates. May also contain small quantities of proprietary performance additives.

Ingredient name	% (w/w)	CAS number
Ethanol	>95.6	64-17-5
Gasoline	1 - 1.5	86290-81-5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Skin contact	Flush contaminated skin with plenty of water. Drench contaminated clothing with water before removing. This is necessary to avoid the risk of sparks from static electricity that could ignite contaminated clothing. Contaminated clothing is a fire hazard. Contaminated leather, particularly footwear, must be discarded. Remove contaminated clothing and shoes. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse health effects persist or are severe.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media	In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.

Product name Ethanol Denatured Fuel Grade

Product code 0000002719 **Page:** 2/13

Version 2 **Date of issue** 4/28/2021

Format Australia
(Australia)

Language ENGLISH
(ENGLISH)

Section 5. Firefighting measures

Specific hazards arising from the chemical

Highly flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Vapours can form explosive mixtures with air. Vapours are heavier than air and can spread along the ground or float on water surfaces to remote ignition sources. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Hazardous thermal decomposition products

Combustion products may include the following:
carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Hazchem code

•3YE

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Immediately contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling. Eliminate all ignition sources.

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill

Eliminate all ignition sources. Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. The method and equipment used must be in conformance with appropriate regulations and industry practice on explosive atmospheres.

Large spill

Eliminate all ignition sources. Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Dike spill area and do not allow product to reach sewage system and surface or ground water. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilt product. The method and equipment used must be in conformance with appropriate regulations and industry practice on explosive atmospheres. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls and personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Ethanol	Safe Work Australia (Australia). TWA: 1880 mg/m ³ 8 hours. Issued/Revised: 5/1995 TWA: 1000 ppm 8 hours. Issued/Revised: 5/1995
Gasoline	ACGIH TLV (United States). TWA: 300 ppm 8 hours. Issued/Revised: 5/1996 TWA: 890 mg/m ³ 8 hours. Issued/Revised: 5/1996 STEL: 500 ppm 15 minutes. Issued/Revised: 5/1996 STEL: 1480 mg/m ³ 15 minutes. Issued/Revised: 5/1996

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is

Product name Ethanol Denatured Fuel Grade

Product code 0000002719

Page: 4/13

Version 2

Date of issue 4/28/2021

Format Australia

Language ENGLISH

(Australia)

(ENGLISH)

Section 8. Exposure controls and personal protection

Environmental exposure controls

important to ensure that all items of personal protective equipment are compatible.

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Chemical splash goggles.

Skin protection

Hand protection

Wear chemical resistant gloves.

Protective gloves must give suitable protection against mechanical risks (i.e. abrasion, blade cut and puncture). Protective gloves will deteriorate over time due to physical and chemical damage. Inspect and replace gloves on a regular basis. The frequency of replacement will depend upon the circumstances of use.

Recommended: Neoprene gloves.

Skin protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Wear suitable protective clothing.

Footwear highly resistant to chemicals.

When there is a risk of ignition wear inherently fire resistant protective clothes and gloves.

When there is a risk of ignition from static electricity, wear anti-static protective clothing. For greatest effectiveness against static electricity, overalls, boots and gloves should all be anti-static.

When the risk of skin exposure is high (from experience this could apply to the following tasks: cleaning work, maintenance and service, filling and transfer, taking samples and cleaning up spillages) then a chemical protective suit and boots will be required.

Work clothing / overalls should be laundered on a regular basis. Laundering of contaminated work clothing should only be done by professional cleaners who have been told about the hazards of the contamination. Always keep contaminated work clothing away from uncontaminated work clothing and uncontaminated personal clothes.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

If there is a requirement for the use of a respiratory protective device, but the use of breathing apparatus (independent of ambient atmosphere) is not required, then a suitable filtering device must be worn.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product.

Recommended: If ventilation is inadequate, use respirator that will protect against organic vapour and dust/mist.

Section 8. Exposure controls and personal protection

Refer to standards:

Respiratory protection:AS/NZS 1715 and AS/NZS 1716
Gloves:AS/NZS 2161.1
Eye protection:AS/NZS 1336 and AS/NZS 1337

Section 9. Physical and chemical properties

Appearance

Physical state	Liquid.
Colour	Clear Colourless.
Odour	Alcohol-like.
Odour threshold	Not available.
pH	Not available.
Melting point	-117°C (-178.6°F)
Boiling point	>35°C (>95°F)
Flash point	Closed cup: 13°C (55.4°F)
Evaporation rate	2.53 (butyl acetate = 1)
Flammability (solid, gas)	Not applicable. Based on - Physical state
Lower and upper explosive (flammable) limits	Lower: 1.4% Upper: 19%
Vapour pressure	9 kPa (67.5 mm Hg) [20°C (68°F)]
Vapour density	1.59 [Air = 1]
Relative density	0.79 [Water = 1]
Solubility	Soluble in water.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	392°C (737.6°F)
Decomposition temperature	Not available.
Viscosity	Not available.

Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame). Avoid excessive heat. Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapour to accumulate in low or confined areas.
Incompatible materials	Reactive or incompatible with the following materials: oxidising materials. peroxides, Ammonia., moisture. Forms explosive mixtures with air. Hygroscopic.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
-------------------------	--------	---------	------	----------

Product name Ethanol Denatured Fuel Grade	Product code 0000002719	Page: 6/13	
Version 2	Date of issue 4/28/2021	Format Australia	Language ENGLISH
		(Australia)	(ENGLISH)

Section 11. Toxicological information

Ethanol	LC50 Inhalation Vapour	Rat	124.7 mg/l	4 hours
	LC50 Inhalation Vapour	Rat	116.9 mg/l	4 hours
	LC50 Inhalation Vapour	Rat	133.8 mg/l	4 hours
Gasoline	LD50 Oral	Rat	10470 mg/kg	-
	LC50 Inhalation Vapour	Rat	>5610 g/m ³	4 hours
	LC50 Inhalation Vapour	Rat	analytical >7630 mg/m ³	4 hours
	LD50 Dermal	Rabbit	Nominal >2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethanol	Skin - Non-irritant to skin.	Rabbit	-	-	-
	Eyes - Cornea opacity	Rabbit	-	-	-
	Eyes - Iris lesion	Rabbit	-	-	-
	Eyes - Irritant	Rabbit	-	-	-
Gasoline	Skin - Irritant	Rabbit	-	-	-
	Eyes - Non-irritating to the eyes.	Rabbit	-	-	-

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Ethanol	Equivalent to OECD 476	Experiment: In vitro Subject: Mammal - species unspecified	Negative
	Equivalent to OECD 473	Experiment: In vitro Subject: Non-mammalian species	Negative
	Equivalent to OECD 478	Experiment: In vivo Subject: Unspecified Cell: Germ	Negative
Gasoline	Equivalent to OECD 476	Experiment: In vitro Subject: Mammal - species unspecified	Negative
	Equivalent to OECD 471	Experiment: In vitro Subject: Non-mammalian species	Negative
	EPA OPPTS 870.5395	Experiment: In vivo Subject: Unspecified Cell: Germ	Negative
	Equivalent to OECD 475	Experiment: In vivo Subject: Unspecified Cell: Germ	Negative

Conclusion/Summary

Not classified. Based on available data, the classification criteria are not met.

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Ethanol	Positive - Oral - Unspecified	Mouse	-	105 weeks
	Negative - Oral - Unspecified	Rat	-	104 weeks
Gasoline	Negative - Inhalation - Unspecified	Rat	-	113 weeks
	Negative - Dermal - Unspecified	Mouse	-	102 weeks

Reproductive toxicity

Product name Ethanol Denatured Fuel Grade

Product code 0000002719

Page: 7/13

Version 2

Date of issue 4/28/2021

Format Australia

Language ENGLISH

(Australia)

(ENGLISH)

Section 11. Toxicological information

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
Ethanol	-	Positive	-	Rat	Oral	2 generation
Gasoline	-	-	Negative	Rat	Inhalation	18 days
	-	Negative	-	Rat	Inhalation	2 generation
	-	-	Negative	Rat	Inhalation	14 days

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Gasoline	Category 3	-	Narcotic effects

Aspiration hazard

Name	Result
Gasoline	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Eye contact	Causes serious eye irritation.
Inhalation	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
Skin contact	No known significant effects or critical hazards.
Ingestion	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	No specific data.
Skin contact	No specific data.
Ingestion	No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact	Vapour, mist or fume may cause eye irritation. Exposure to vapour, mist or fume may cause stinging, redness and watering of the eyes.
Inhalation	May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs. Vapour, mist or fume may irritate the nose, mouth and respiratory tract.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Ingestion	If swallowed, may irritate the mouth, throat and digestive system. If swallowed, may cause headaches, dizziness, drowsiness and nausea, and may lead to unconsciousness.
General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

Product name Ethanol Denatured Fuel Grade

Product code 0000002719 **Page:** 8/13

Version 2 **Date of issue** 4/28/2021

Format Australia
(Australia)

Language ENGLISH
(ENGLISH)

Section 11. Toxicological information

Other information

Ethanol - Human data: In humans excessive consumption of alcoholic beverages during pregnancy is associated with the induction of Fetal Alcohol Syndrome in the offspring. Reduced birth weight and physical and mental defects occur. There is no evidence that such effects might be caused by exposures other than direct ingestion of alcoholic drinks. In humans high lifetime consumption of alcoholic beverages can be associated with certain cancers and effects on the liver. There is no evidence that these can be caused by exposure other than direct ingestion of alcoholic drinks (IARC 1988).

Petrol - Excess exposure to vapors may produce headaches, dizziness, nausea, drowsiness, irritation of eyes, nose and throat and central nervous system depression. Aspiration of this material into the lungs can cause chemical pneumonia and can be fatal. Aspiration into the lungs can occur while vomiting after ingestion of this product. Inhalation of unleaded gasoline vapors did not produce birth defects in laboratory animals. Ingestion of this material can cause gastrointestinal irritation and diarrhea.

In a long-term inhalation study of whole unleaded gasoline vapors, exposure-related kidney damage and kidney tumors were observed in male rats. Similar kidney effects were not seen in female rats or in mice. At the highest exposure level (2056 ppm), female mice had an increased incidence of liver tumors. Results from subsequent scientific studies have shown that a broad variety of chemicals cause these kidney effects only in the male rat. Further studies have discovered the means by which the physiology of the male rat uniquely predispose it to these effects. Consequently, the Risk Assessment Forum of the Environmental Protection Agency has recognized that these responses are not predictive of a human health hazard. The liver tumors that were increased in the high-dose female mice are likewise of questionable significance because of their high spontaneous occurrence even without chemical exposure and because the rate of their occurrence is accelerated by a broad spectrum of chemicals not commonly considered to be carcinogens (e.g., phenobarbital). Thus, the significance of the mouse liver tumor response in terms of human health is questionable.

Gasoline is a complex mixture of hydrocarbons and contains benzene (typically no more than 2 volume%), toluene, and xylene. Chronic exposure to high levels of benzene has been shown to cause cancer (leukemia) in humans and other adverse blood effects (anemia). Benzene is considered a human carcinogen by IARC, NTP and OSHA. Over exposure to xylene and toluene can cause irritation to the upper respiratory tract, headache and narcosis. Some liver damage and lung inflammation were seen in chronic studies on xylene in guinea pigs but not in rats.

Solvent "sniffing" (abuse) or intentional overexposure to vapors can produce serious central nervous system effects, including unconsciousness, and possibly death.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
-------------------------	--------	---------	----------

Product name Ethanol Denatured Fuel Grade

Product code 0000002719

Page: 9/13

Version 2 **Date of issue** 4/28/2021

Format Australia

Language ENGLISH

(Australia)

(ENGLISH)

Section 12. Ecological information

Ethanol	EC50 675 mg/l	Algae	4 days
	EC50 4432 mg/l	Aquatic plants	7 days
	Acute LC50 5012 mg/l	Daphnia	48 hours
	Acute LC50 153 g/l	Fish	96 hours
	Acute LC50 14.2 g/l	Fish	96 hours
Gasoline	Chronic LC50 2 mg/l	Daphnia	10 days
	Chronic LC50 9.6 mg/l	Daphnia	9 days
	Acute EC50 15.41 mg/l Nominal Fresh water	Micro-organism	40 hours
	Acute EL50 3.1 mg/l Nominal Fresh water	Algae	72 hours
	Acute EL50 3.7 mg/l Nominal Fresh water	Algae	96 hours
	Acute EL50 4.5 mg/l Nominal Fresh water	Daphnia	48 hours
	Acute LL50 10 mg/l Nominal Fresh water	Fish	96 hours
	Acute LL50 8.2 mg/l Nominal Fresh water	Fish	96 hours
	Acute NOELR 0.5 mg/l Nominal Fresh water	Algae	72 hours
	Acute NOELR 0.5 mg/l Nominal Fresh water	Daphnia	48 hours
	Chronic EL50 10 mg/l Nominal Fresh water	Daphnia	21 days
	Chronic EL50 >40 mg/l Nominal Fresh water	Daphnia	21 days
	Chronic EL50 10 mg/l Nominal Fresh water	Fish	21 days
	Chronic LL50 5.2 mg/l Nominal Fresh water	Fish	14 days
	Chronic NOELR 2.6 mg/l Nominal Fresh water	Daphnia	21 days
	Chronic NOELR 16 mg/l Nominal Fresh water	Daphnia	21 days
	Chronic NOELR 2.6 mg/l Nominal Fresh water	Fish	14 days
	Chronic NOELR 2.6 mg/l Nominal Fresh water	Fish	21 days
	Chronic PNEC >0.4 mg/kg	soil, plants	-

Persistence and degradability

Inherently biodegradable

Product/ingredient name	Test	Result	Dose	Inoculum
Ethanol	EPA	95 % - Readily - 15 days	-	-
	EPA	84 % - Readily - 20 days	-	-
	EPA	74 % - Readily - 5 days	-	-
	EPA	74 % - Readily - 10 days	-	-
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability	
Ethanol	-	-	Readily	

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogP _{ow}	BCF	Potential
Ethanol	-0.35	-	low
Gasoline	2 to 7	-	high

Section 12. Ecological information

Mobility in soil

Soil/water partition coefficient (K_{oc})

Not available.

Mobility

The product will dissolve rapidly in water.
Ethanol: Soluble in water. Gasoline: Very slightly soluble in water.
If released to soil the product will rapidly evaporate into the atmosphere. The product is poorly absorbed onto soils or sediments. Spillages may penetrate the soil causing ground water contamination.

Other ecological information

Gasoline: Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.

Special Precautions for Landfill or Incineration

No additional special precautions identified.

Section 14. Transport information

	ADG	IMDG	IATA
UN number	UN3475	UN3475	UN3475
UN proper shipping name	ETHANOL AND GASOLINE MIXTURE	ETHANOL AND GASOLINE MIXTURE	Ethanol and gasoline mixture
Transport hazard class(es)	3 	3 	3 
Packing group	II	II	II
Environmental hazards	No.	No.	No.
Additional information	Hazchem code •3YE Special provisions 333	Emergency schedules F-E, S-E Special provisions 333, 363	Quantity limitation Passenger and Cargo Aircraft: 5 L. Packaging instructions: 353. Cargo Aircraft Only: 60 L. Packaging instructions: 364. Limited Quantities - Passenger Aircraft: 1 L. Packaging instructions: Y341. Special provisions A156

Product name Ethanol Denatured Fuel Grade

Product code 0000002719 Page: 11/13

Version 2 Date of issue 4/28/2021

Format Australia
(Australia)

Language ENGLISH
(ENGLISH)

Section 14. Transport information

Special precautions for user Not available.

Section 15. Regulatory information

Standard for the Uniform Scheduling of Medicines and Poisons

Not scheduled

Industrial Products - Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with NOSHC National Code of Practice for labelling of workplace substances.

Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

Montreal Protocol

Ingredient name	List name	Status
Not listed.		

Stockholm Convention on Persistent Organic Pollutants

Ingredient name	List name	Status
Not listed.		

Rotterdam Convention on Prior Informed Consent (PIC)

Ingredient name	List name	Status
Not listed.		

International lists

National inventory

REACH Status

For the REACH status of this product please consult your company contact, as identified in Section 1.

Australia inventory (AICS)

Contact supplier for regulatory information.

Canada inventory

Not determined.

China inventory (IECSC)

Not determined.

Japan inventory (ENCs)

Not determined.

Korea inventory (KECI)

Not determined.

Philippines inventory (PICCS)

Not determined.

Taiwan Chemical Substances Inventory (TCSI)

Not determined.

United States inventory (TSCA 8b)

Not determined.

Section 16. Any other relevant information

History

Date of printing	4/28/2021
Date of issue/Date of revision	4/28/2021
Date of previous issue	10 November 2009
Version	2
Prepared by	Product Stewardship

Product name Ethanol Denatured Fuel Grade

Product code 0000002719

Page: 12/13

Version 2 **Date of issue** 4/28/2021

Format Australia
(Australia)

Language ENGLISH
(ENGLISH)

Section 16. Any other relevant information

Key to abbreviations

ADG = Australian Dangerous Goods
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NOHSC = National Occupational Health and Safety Commission
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
STEL = Short term exposure limit
SUSMP = Standard Uniform Schedule of Medicine and Poisons
UN = United Nations
TWA = Time weighted average
VOC = Volatile Organic Compound
SADT = Self-Accelerating Decomposition Temperature
Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A	On basis of test data Calculation method

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Ethanol Denatured Fuel Grade

Product code 0000002719 Page: 13/13

Version 2 Date of issue 4/28/2021

Format Australia

Language ENGLISH

(Australia)

(ENGLISH)